

Version: 6 / GB Date revised: 15.08.2023

Substance number: 21075006584 Replaces Version: 5 / GB Print date: 15.11.2024



# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Marabu do it Glitter 584, 150 ml

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/preparation

Colour spray

#### 1.3. Details of the supplier of the safety data sheet

#### Address/Manufacturer

Marabu GmbH & Co. KG

Asperger Strasse 4

71732 Tamm

Deutschland

Telephone no. +49-7141/691-0

Information provided Department product safety

by / telephone

E-mail address of

PRSI@marabu.com

person responsible

for this SDS

Information provided Department product safety

by / telephone

E-mail address of

PRSI@marabu.com

person responsible

for this SDS

## 1.4. Emergency telephone number

(+49) (0)621-60-43333

# **SECTION 2: Hazards identification \*\*\***

#### 2.1. Classification of the substance or mixture

#### Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)

Aerosol 1 H222


H229

Eve Irrit. 2 H319 STOT SE 3 H336

# 2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

**Hazard pictograms** 





Print date: 15.11.2024 Substance number: 21075006584 Replaces Version: 5 / GB



#### Signal word

Danger

#### **Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurized container: may burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

## **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use. Wash hands thoroughly after handling. P264.1

P271 Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection. P280 P305+P351+P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

Store locked up. P405

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501.9 Dispose of contents/container as problematic waste.

#### Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains Ethyl acetate; Propan-2-ol; n-Butyl acetate; 2-Methoxy-1-methylethyl acetate

## Supplemental information

**EUH066** Repeated exposure may cause skin dryness or cracking.

# **Further supplemental information**

Without adequate ventilation, explosive atmosphere/gas mix may be created.

#### 2.3. Other hazards

Pressurized container. At temperatures above 50 °C, deformation and explosion possible, resulting in serious physical injury. Vapours are heavier than air and may therefore form flammable and explosive mixtures with air, even at temperatures below 0 °C. Use in inadequately ventilated areas Environments may cause breathing problems, drowsiness and, in severe cases, unconsciousness.

The product contains no PBT substances. The product contains no vPvB substances. This product does not contain a substance that has endocrine disrupting properties with respect to human. The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

**Hazardous ingredients** 

Page: 2 (25)



Trade name: Marabu do it Glitter 584, 150 ml

Version: 6 / GB Date revised: 15.08.2023

Substance number: 21075006584 Replaces Version: 5 / GB Print date: 15.11.2024

**Ethyl acetate** 

CAS No. 141-78-6 EINECS no. 205-500-4

Registration no. 01-2119475103-46

Concentration >= 25 < 50 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 2 H225 Eye Irrit. 2 H319 STOT SE 3 H336

Propan-2-ol

CAS No. 67-63-0 EINECS no. 200-661-7

Registration no. 01-2119457558-25

Concentration >= 10 < 20 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 2 H225 Eye Irrit. 2 H319 STOT SE 3 H336

n-Butyl acetate

CAS No. 123-86-4 EINECS no. 204-658-1

Registration no. 01-2119485493-29

Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3 H226 STOT SE 3 H336

2-Butoxyethanol

CAS No. 111-76-2 EINECS no. 203-905-0

Registration no. 01-2119475108-36

Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

 Skin Irrit. 2
 H315

 Acute Tox. 3
 H331

 Acute Tox. 4
 H312

 Acute Tox. 4
 H302


 Eye Irrit. 2
 H319

ATE oral 1.200 mg/kg cATpE dermal 1.100 mg/kg cATpE inhalative, Dust/Mist 0.5 mg/l ATE inhalative, Vapors mg/l 3

2-Methoxy-1-methylethyl acetate

CAS No. 108-65-6 EINECS no. 203-603-9

Registration no. 01-2119475791-29



Version: 6 / GB Date revised: 15.08.2023

Substance number: 21075006584 Replaces Version: 5 / GB Print date: 15.11.2024

Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3 H226 STOT SE 3 H336

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

#### **General information**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

#### After inhalation

Remove affected person from danger area. Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Summon a doctor immediately.

#### After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. Consult a doctor if skin irritation persists.

#### After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

#### After ingestion

As the product is in a pressurised gas container, ingestion is not expected. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting. Summon a doctor immediately.

#### Adhere to personal protective measures when giving first aid

Use personal protective equipment in case of possible contact with the product (see section 8).

## 4.2. Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11. Further symptoms are possible.

# 4.3. Indication of any immediate medical attention and special treatment needed

#### Hints for the physician / treatment

Treat symptomatically

# **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

#### Suitable extinguishing media

Aalcohol resistant foam, CO2, powders, water spray/mist

#### Non suitable extinguishing media


water iet

#### 5.2. Special hazards arising from the substance or mixture

In the event of fire the following can be released: Carbon monoxide (CO); Carbon dioxide (CO2); dense black smoke; Exposure to decomposition products may cause a health hazard. Appropriate breathing









Substance number: 21075006584 Replaces Version: 5 / GB Print date: 15.11.2024



apparatus may be required.

# 5.3. Advice for firefighters

#### Special protective equipment for fire-fighting

Use self-contained breathing apparatus. Wear full chemical protective clothing. Fire fighter's clothing must conform to European standard EN469.

#### Other information

Cool endangered containers with water spray jet. Do not allow run-off from fire fighting to enter drains or water courses.

# **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Keep away sources of ignition. Remove persons to safety. Ensure adequate ventilation. Keep away unprotected persons. Avoid contact with skin, eyes and clothing. Do not breathe gas/fumes/vapour/spray. For emergency responders: Wear personal protective equipment. Use breathing apparatus if exposed to vapours/dust/aerosol.

#### 6.2. Environmental precautions

Do not allow to enter drains or waterways. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

# 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

#### 6.4. Reference to other sections

Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Provide good ventilation of working area (local exhaust ventilation if necessary). In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Isolate from sources of heat, sparks and open flame. Avoid skin and eye contact. Avoid the inhalation of particulates and spray mist arising from the application of this mixture. Smoking, eating and drinking shall be prohibited in application area. For personal protection see Section 8. Comply with the health and safety at work laws. Do not allow to enter drains or water courses.

# Advice on protection against fire and explosion

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Keep away from sources of ignition - No smoking. Take action to prevent static discharges. Do not spray on a naked flame or any incandescent material. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. With conveying and handling possibilty of electrostatic charges.

Trade name: Marabu do it Glitter 584, 150 ml

Version: 6 / GB Date revised: 15.08.2023

Substance number: 21075006584 Replaces Version: 5 / GB Print date: 15.11.2024



Classification of fires C (Flammable gases)

Temperature class T2

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Store in accordance with national regulation

#### Further information on storage conditions

Observe label precautions. Keep in original containers. Keep container dry in a cool, well-ventilated place. Protect from direct sunlight. Protect from warmth. Keep away from sources of ignition. No smoking. Prevent unauthorised access.

# 7.3. Specific end use(s)

Colour spray

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

#### **Exposure limit values**

Ethyl	acatata
⊏tnvi	acetate

List	EH40	
Type	WEL	
Value	200	ppm(V)

Short term exposure limit 400 ppm(V)

Status: 2011

**Ethyl acetate** 

List

LIST	EU			
Value	734	mg/m³	200	ppm(V)
Short term exposure limit	1468	mg/m³	400	ppm(V)

\_,,

EH40

Remarks: (EU) 2017/164

#### 2-Methoxy-1-methylethyl acetate

Туре	WEL			
Value	274	mg/m³	50	ppm(V)
Short term exposure limit	548	mg/m³	100	ppm(V)

Skin resorption / sensibilisation: Sk2011

#### 2-Methoxy-1-methylethyl acetate

List	EU			
Value	275	mg/m³	50	ppm(V)
Short term exposure limit	550	mg/m³	100	ppm(V)

Skin resorption / sensibilisation: SkinRemarks: 2000/39/EG

Propan-2-ol

List	EH40			
Type	WEL			
Value	999	mg/m³	400	ppm(V)
Short term exposure limit	1250	mg/m³	500	ppm(V)
01-1 - 0044				

Status: 2011



Trade name: Marabu do it Glitter 584, 150 ml

Version: 6 / GB Date revised: 15.08.2023

Substance number: 21075006584 Replaces Version: 5 / GB Print date: 15.11.2024

2-Butoxyethanol

List EH40 Type WEL

Value 25 ppm(V) Short term exposure limit 50 ppm(V)

Skin resorption / sensibilisation: Sk2011

2-Butoxyethanol

List EU

Value 98  $mg/m^3$  20 ppm(V)Short term exposure limit 246  $mg/m^3$  50 ppm(V)

Skin resorption / sensibilisation: SkinRemarks: 2000/39/EG

n-Butyl acetate

List EH40 Type WEL

Value 724  $mg/m^3$  150 ppm(V)Short term exposure limit 966  $mg/m^3$  200 ppm(V)

Status: 2011

n-Butyl acetate

List EU

Value 241  $mg/m^3$  50 ppm(V)Short term exposure limit 723  $mg/m^3$  150 ppm(V)

Remarks: (EU) 2019/1831

**Derived No/Minimal Effect Levels (DNEL/DMEL)** 

**Ethyl acetate** 

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Acute
Route of exposure inhalative

Concentration 1468 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Acute
Route of exposure inhalative
Mode of action Local effects

Concentration 1468 g/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Worker Route of exposure dermal

Mode of action Chronic effects

Concentration 63 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Route of exposure inhalative
Mode of action Chronic effects



Trade name: Marabu do it Glitter 584, 150 ml

Version: 6 / GB Date revised: 15.08.2023

Substance number: 21075006584 Replaces Version: 5 / GB Print date: 15.11.2024

Concentration 734 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Route of exposure inhalative
Mode of action Chronic effects

Concentration 734 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Route of exposure inhalative
Mode of action Acute effects

Concentration 734 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Route of exposure inhalative
Mode of action Local effects

Concentration 734 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Consumer Route of exposure dermal

Mode of action Chronic effects

Concentration 37 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Route of exposure inhalative
Mode of action Chronic effects

Concentration 367 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Consumer Route of exposure oral

Mode of action Chronic effects

Concentration 4,5 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Route of exposure inhalative
Mode of action Local effects

Concentration 367 mg/m<sup>3</sup>

Propan-2-ol

Type of value Derived No Effect Level (DNEL)

Reference group Worker

Duration of exposure Long term



Trade name: Marabu do it Glitter 584, 150 ml

Version: 6 / GB Date revised: 15.08.2023

Substance number: 21075006584 Replaces Version: 5 / GB Print date: 15.11.2024

Route of exposure inhalative

Mode of action Systemic effects

Concentration 500 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 888 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure Long term Route of exposure inhalative

Mode of action Systemic effects

Concentration 89 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure Long term Route of exposure dermal

Mode of action Systemic effects

Concentration 319 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure Long term Route of exposure oral

Mode of action Systemic effects

Concentration 26 mg/kg/d

#### 2-Methoxy-1-methylethyl acetate

Type of value Derived No Effect Level (DNEL)

Reference group Worker

Duration of exposure Long term

Route of exposure dermal

Mode of action Systemic effects

Concentration 796 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Worker

Duration of exposure Long term

Route of exposure inhalative

Mode of action Systemic effects

Concentration 275 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)



Trade name: Marabu do it Glitter 584, 150 ml

Version: 6 / GB Date revised: 15.08.2023

Substance number: 21075006584 Replaces Version: 5 / GB Print date: 15.11.2024

Reference group Consumer
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 320 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long term

Route of exposure inhalative

Mode of action Systemic effects

Concentration 33 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long term

Route of exposure inhalative

Mode of action Local effects

Concentration 33 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long term

Route of exposure oral

Mode of action Systemic effects

Concentration 36 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Worker

Duration of exposure Lifetime

Route of exposure inhalative

Mode of action Local effects

Concentration 550 mg/m<sup>3</sup>

2-Butoxyethanol

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Acute
Route of exposure dermal

Mode of action Systemic effects

Concentration 89 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Worker

Duration of exposure Short term

Route of exposure inhalative

Mode of action Systemic effects

Concentration 1091 mg/m<sup>3</sup>

Page: 10 (25)



Trade name: Marabu do it Glitter 584, 150 ml

Version: 6 / GB Date revised: 15.08.2023

Substance number: 21075006584 Replaces Version: 5 / GB Print date: 15.11.2024

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure Short term
Route of exposure inhalative
Mode of action Local effects

Concentration 147 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Worker

Duration of exposure Long term

Route of exposure dermal

Mode of action Systemic effects

Concentration 125 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Worker

Duration of exposure Long term

Route of exposure inhalative

Mode of action Systemic effects

Concentration 98 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Acute

Route of exposure dermal

Mode of action Systemic effects

Concentration 89,5 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Acute
Route of exposure inhalative

Mode of action Systemic effects

Concentration 426 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Acute

Route of exposure oral

Mode of action Systemic effects

Concentration 26,7 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Consumer

Acute
inhalative
Local effects

Page: 11 (25)



Trade name: Marabu do it Glitter 584, 150 ml

Version: 6 / GB Date revised: 15.08.2023

Substance number: 21075006584 Replaces Version: 5 / GB Print date: 15.11.2024

Concentration 147 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long term

Route of exposure dermal

Mode of action Systemic effects

Concentration 75 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long term

Route of exposure inhalative

Mode of action Systemic effects

Concentration 59 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long term

Route of exposure oral

Mode of action Systemic effects

Concentration 6,3 mg/kg

n-Butyl acetate

Type of value Derived No Effect Level (DNEL)

Reference group Worker

Duration of exposure Short term

Route of exposure inhalative

Mode of action Systemic effects

Concentration 600 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Worker

Duration of exposure Short term

Route of exposure inhalative

Mode of action Local effects

Concentration 600 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Worker

Duration of exposure Long term

Route of exposure inhalative

Mode of action Systemic effects

Concentration 300 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Worker

Duration of exposure Long term

Page: 12 (25)



Trade name: Marabu do it Glitter 584, 150 ml

Version: 6 / GB Date revised: 15.08.2023

Substance number: 21075006584 Replaces Version: 5 / GB Print date: 15.11.2024

Route of exposure inhalative

Mode of action Local effects

Concentration 300 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Short term

Route of exposure inhalative

Mode of action Systemic effects

Concentration 300 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Short term

Route of exposure inhalative

Mode of action Local effects

Concentration 300 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long term

Route of exposure inhalative

Made of action Systemic of

Mode of action Systemic effects

Concentration 35,7 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term
Route of exposure inhalative
Mode of action Local effects

Concentration 35,7 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Worker

Duration of exposure Long term

Route of exposure dermal

Mode of action Systemic effects

Concentration 11 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Worker

Duration of exposure Short term

Route of exposure dermal

Mode of action Systemic effects

Concentration 11 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Page: 13 (25)



Trade name: Marabu do it Glitter 584, 150 ml

Version: 6 / GB Date revised: 15.08.2023

Substance number: 21075006584 Replaces Version: 5 / GB Print date: 15.11.2024

Duration of exposure Long term Route of exposure dermal

Mode of action Systemic effects

Concentration 6 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Short term

Route of exposure dermal

Mode of action Systemic effects

Concentration 6 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long term

Route of exposure oral

Mode of action Systemic effects

Concentration 2 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Short term

Route of exposure oral

Mode of action Systemic effects

Concentration 2 mg/kg/d

# **Predicted No Effect Concentration (PNEC)**

**Ethyl acetate** 

Type of value PNEC
Type Water

Concentration 0,26 mg/l

Type of value PNEC Type Aquatic

Concentration 0,026 mg/l

Type of value PNEC

Type Freshwater sediment

Concentration 0,34 mg/kg

Type of value PNEC

Type Marine sediment

Concentration 0,034 mg/kg

Type of value PNEC Type Soil

Concentration 0,22 mg/kg

Page: 14 (25)



Trade name: Marabu do it Glitter 584, 150 ml

Version: 6 / GB Date revised: 15.08.2023

Substance number: 21075006584 Replaces Version: 5 / GB Print date: 15.11.2024

Propan-2-ol

Type of value PNEC
Type Freshwater

Concentration 140,9 mg/l

Type of value PNEC
Type Saltwater

Concentration 140,9 mg/l

Type of value PNEC

Type Sewage treatment plant (STP)

Concentration 2251 mg/l

Type of value PNEC

Type Freshwater sediment

Concentration 552 mg/kg

Type of value PNEC

Type Marine sediment

Concentration 552 mg/kg

Type of value PNEC Type Soil

Concentration 28 mg/kg

2-Methoxy-1-methylethyl acetate

Reference substance 2-Methoxy-1-methylethyl acetate

Type of value PNEC
Type Freshwater

Concentration 0,635 mg/l

Type of value PNEC

Type Freshwater sediment

Concentration 3,29 mg/kg

Type of value PNEC Type Soil

Concentration 0,29 mg/kg

Source Literature value

Type of value PNEC

Type Sewage treatment plant (STP)

Concentration 100 mg/l

Source Literature value

Type of value PNEC

Page: 15 (25)



Trade name: Marabu do it Glitter 584, 150 ml

Version: 6 / GB Date revised: 15.08.2023

Substance number: 21075006584 Replaces Version: 5 / GB Print date: 15.11.2024

Type Marine sediment

Concentration 0,329 mg/kg

Source Literature value

Type of value PNEC
Type Saltwater

Concentration 0,0635 mg/l

Type of value PNEC

Type Water (intermittent release)

Concentration 6,35 mg/l

2-Butoxyethanol

Type of value PNEC
Type Freshwater

Concentration 8,8 mg/l

Type of value PNEC Type Soil

Concentration 2,8 mg/kg

Type of value PNEC

Type Freshwater sediment

Concentration 34,6 mg/kg

Type of value PNEC

Type Sewage treatment plant (STP)

Concentration 463 mg/l

Type of value PNEC
Type Saltwater

Concentration 0,88 mg/l

Type of value PNEC

Type Marine sediment

Concentration 3,46 mg/kg

n-Butyl acetate


Type of value PNEC
Type Freshwater

Concentration 0,18 mg/l

Type of value PNEC
Type Saltwater

Concentration 0,018 mg/l

Page: 16 (25)



Version: 6 / GB Date revised: 15.08.2023

Substance number: 21075006584 Replaces Version: 5 / GB Print date: 15.11.2024

Type of value

PNEC

Type

Freshwater sediment

Concentration

0,981 mg/kg

Type of value

PNEC

Type

Marine sediment

Concentration

0,0981

mg/kg

Type of value Type PNEC Soil

Concentration

0.0903

mg/kg

Type of value

PNEC

Type

Sewage treatment plant (STP)

Concentration

35,6

mg/l

Type of value

PNEC

Type

Water (intermittent release)

Concentration

0,36

mg/l

## 8.2. Exposure controls

# **Exposure controls**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

#### General protective and hygiene measures

Observe the usual precautions for handling chemicals. Keep away from food, drink and animal feedingstuffs. Do not inhale gases/vapours/aerosols. Avoid contact with skin and eyes. Wash hands and / or face before breaks and after work. Take off dirty, soaked clothes immediately. Wash soiled clothing before re-use. Store work clothing separately.

## **Respiratory protection**

If workers could be exposed to concentrations above the exposure limit they should use a respirator to EN 140, fitted with a filter suitable for both particulates and vapours, to EN 14387, with an assigned protection factor of at least 10 (e.g. A2P3) Selection of any respiratory protective equipment should ensure that it is adequate to reduce exposure to protect the worker's health and is suitable for the wearer, task and environment, including consideration of the facial features of the wearer.

#### **Hand protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

Use gloves tested according to EN ISO 374.

For prolonged or repeated handling, use Appropriate Material Butyl rubber


Material thickness > 0,7 mm
Breakthrough time > 30 min

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.


Page: 17 (25)





Version: 6 / GB Date revised: 15.08.2023

Substance number: 21075006584 Replaces Version: 5 / GB Print date: 15.11.2024



The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

mamenance.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

#### Eye protection

Use safety eyewear tested according to EN ISO 16321-1 designed to protect against splash of liquids.

#### **Body protection**

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre. Cotton or cotton/synthetic overalls are normally suitable.

#### **Environmental exposure controls**

Do not allow to enter drains or water courses. If the legally prescribed emission limits are exceeded, a suitable exhaust air purification system must be installed.

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state Aerosol

Colourgold colouredOdoursolvent-like

**Melting point** 

Remarks Not applicable due to nature of the product

Freezing point

Remarks Not applicable due to nature of the product

#### Boiling point or initial boiling point and boiling range

Reference substance Ethyl acetate

Value appr. 76 °C

Pressure 1.013 hPa Source Literature value

#### **Flammability**

Extremely flammable aerosol.

#### Upper and lower explosive limits

Reference substance n-Butyl acetate

Lower explosion limit appr. 1,2 %(V)

Reference substance n-Butyl acetate

Upper explosion limit appr. 15 %(V)

Source Literature value

Flash point

Value < 0 °C


**Auto-ignition temperature** 

Value appr. 415 °C

Source Literature value

Page: 18 (25)





Version: 6 / GB Date revised: 15.08.2023

Substance number: 21075006584 Replaces Version: 5 / GB Print date: 15.11.2024

**Decomposition temperature** 

Remarks not determined

pH value

Remarks Not applicable

Remarks substance/mixture is non-soluble (in water)

**Viscosity** 

Remarks

Remarks not determined

Solubility(ies)

Remarks Not applicable due to nature of the product

Partition coefficient n-octanol/water (log value)

Remarks Not applicable due to nature of the product

Vapour pressure

Remarks Not applicable due to nature of the product

Density and/or relative density

Value 0,75 g/cm<sup>3</sup>

Temperature 20 °C

Relative vapour density

Value > 1

**Particle characteristics** 

Remarks Not applicable due to nature of the product

#### 9.2. Other information

#### Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No hazardous reactions when stored and handled according to prescribed instructions.

#### 10.2. Chemical stability

Stable at temperatures below 50 °C.

#### 10.3. Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

# 10.4. Conditions to avoid

Protect from heat and direct sunlight. When exposed to high temperatures may produce hazardous decomposition products. Avoid damage to the aerosol containers, for example by falling down. Never pierce aerosol containers, even after use. Avoid high concentrations of solvent vapours. Observe the notes on ventilation (section 8).


#### 10.5. Incompatible materials

Oxidising agents, strongly alkaline substances, Strongly acidic substances

# 10.6. Hazardous decomposition products

Page: 19 (25)





Date revised: 15.08.2023

Substance number: 21075006584 Replaces Version: 5 / GB Print date: 15.11.2024

Version: 6 / GB

See chapter 5.2 (Firefighting measures - Special hazards arising from the substance or mixture). No decomposition during intended use (see section 1).

# **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute oral toxicity** 

ATE > 2.000 mg/kg
Method calculated value (Regulation (EC) No. 1272/2008)

**Acute oral toxicity (Components)** 

2-Butoxyethanol

ATE 1200 mg/kg

n-Butyl acetate

Species rat (female)

LD50 10760 mg/kg

Method OECD 423

**Acute dermal toxicity** 

ATE > 2.000 mg/kg

Method calculated value (Regulation (EC) No. 1272/2008)

**Acute dermal toxicity (Components)** 

n-Butyl acetate

Species Rats (male/female)

LD50 14112 mg/kg

Method OECD 402

Acute inhalational toxicity

ATE > 20 mg/l

Administration/Form Vapors

Method calculated value (Regulation (EC) No. 1272/2008)

ATE > 5 mg/l

Administration/Form Dust/Mist

Method calculated value (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

**Acute inhalative toxicity (Components)** 

n-Butyl acetate

Species Rats (male/female)

LC50 > 21 mg/l

Duration of exposure 4 h Method OECD 403

2-Butoxyethanol

ATE 3 mg/l


Administration/Form Vapors

Skin corrosion/irritation

Remarks Based on available data, the classification criteria are not met.

Skin corrosion/irritation (Components)

Page: 20 (25)



Version: 6 / GB Date revised: 15.08.2023

Substance number: 21075006584 Replaces Version: 5 / GB Print date: 15.11.2024

2-Methoxy-1-methylethyl acetate

Species rabbit evaluation non-irritant

Serious eye damage/irritation

evaluation irritant

Remarks The classification criteria are met.

Sensitization

Remarks Based on available data, the classification criteria are not met.

**Sensitization (Components)** 

2-Butoxyethanol

Route of exposure dermal
Species guinea pig
evaluation non-sensitizing

Mutagenicity

Remarks Based on available data, the classification criteria are not met.

Reproductive toxicity

Remarks Based on available data, the classification criteria are not met.

Carcinogenicity

Remarks Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity (STOT)** 

Single exposure

Remarks The classification criteria are met. evaluation May cause drowsiness or dizziness.

Repeated exposure

Remarks Based on available data, the classification criteria are not met.

**Aspiration hazard** 

Based on available data, the classification criteria are not met.

#### 11.2. Information on other hazards

#### **Endocrine disrupting properties with respect to humans**

The product does not contain a substance that has endocrine disrupting properties with respect to humans.

#### **Experience in practice**

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation. Ingestion may cause nausea, diarrhoea and vomiting.


#### Other information

There are no data available on the mixture itself.

The mixture has been assessed following the additivity method of the CLP Regulation (EC) No 1272/2008 and classified for toxicological hazards accordingly.

Page: 21 (25)





Version: 6 / GB Date revised: 15.08.2023

Substance number: 21075006584 Replaces Version: 5 / GB Print date: 15.11.2024



# **SECTION 12: Ecological information**

#### 12.1. Toxicity

#### **General information**

There are no data available on the mixture itself.Do not allow to enter drains or water courses.The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as dangerous for the environment.

# 12.2. Persistence and degradability

#### **General information**

There are no data available on the mixture itself.

#### 12.3. Bioaccumulative potential

#### **General information**

There are no data available on the mixture itself.

#### Partition coefficient n-octanol/water (log value)

Remarks Not applicable due to nature of the product

# 12.4. Mobility in soil

#### **General information**

There are no data available on the mixture itself.

#### 12.5. Results of PBT and vPvB assessment

#### **General information**

There are no data available on the mixture itself.

#### Results of PBT and vPvB assessment

The product contains no PBT substances

The product contains no vPvB substances.

#### 12.6 Endocrine disrupting properties

#### Endocrine disrupting properties with respect to the envrionment

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

#### 12.7. Other adverse effects

#### **General information**

There are no data available on the mixture itself.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### Disposal recommendations for the product

Do not allow to enter drains or water courses.

Wastes and emptied containers should be classified in accordance with relevant national regulation.

The European Waste Catalogue classification of this product, when disposed of as waste is


EWC waste code 08 01 11\* waste paint and varnish containing organic solvers.

waste paint and varnish containing organic solvents or other dangerous substances

Page: 22 (25)



Trade name: Marabu do it Glitter 584, 150 ml



Substance number: 21075006584 Replaces Version: 5 / GB Print date: 15.11.2024

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information contact your local waste authority.

#### Disposal recommendations for packaging

Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Not emptied containers are hazardous waste.

EWC waste code 15 01 10\* packaging containing residues of or contaminated by

dangerous substances

# **SECTION 14: Transport information**

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
14.1. UN number	1950	1950	1950
14.2. UN proper shipping name	AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)	2	2.1	2.1
Label	8	8	8
Limited Quantity	11	11	
Transport category	2		
14.5. Environmental hazards	-		
Tunnel restriction code	D		

# Information for all modes of transport

# 14.6. Special precautions for user

Transport within the user's premises:

Always transport in closed containers that are upright and secure.

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

#### Other information


14.7. Maritime transport in bulk according to IMO instruments

Not applicable

# **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC





Print date: 15.11.2024 Substance number: 21075006584 Replaces Version: 5 / GB

> VOC (CH) 84.93 % 637 g/l VOC (EU) 84.93 % 637 g/l

#### Other regulations, restrictions and prohibition regulations

The product complies with the requirements of the Persistent Organic Pollutants Regulation 2019/1021. The product complies with the requirements of Regulation 2024/590 on substances that deplete the ozone

layer.

The product is not subject to Regulation 649/2012 on the export and import of dangerous chemicals.

#### Other information

The product does not contain substances of very high concern (SVHC).

#### 15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

# **SECTION 16: Other information**

#### Hazard statements listed in Chapter 3

H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H229

Pressurized container: may burst if heated.

H302 Harmful if swallowed.

H312 Harmful in contact with skin. Causes skin irritation. H315

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H336 May cause drowsiness or dizziness.

#### CLP categories listed in Chapter 3

Acute Tox. 3 Acute toxicity, Category 3 Acute Tox. 4 Acute toxicity, Category 4 Aerosol 1 Aerosol, Category 1 Eye Irrit. 2 Eye irritation, Category 2 Flam. Liq. 2 Flammable liquid, Category 2 Flam. Liq. 3 Flammable liquid, Category 3 Skin Irrit. 2 Skin irritation, Category 2

STOT SE 3 Specific target organ toxicity - single exposure, Category 3

#### **Abbreviations**

ADR: Accord européen relatif au transport international des marchandises Dangereuses par Route RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses

GGVSee: Gefahrgutverordnung See

IMDG: International Maritime Code for Dangerous Goods

ICAO: International Civil Aviation Organization IATA: International Air Transport Association

CAS: Chemical Abstracts Service

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

EmS: Emergency Schedules

AICS: Australian Inventory of Chemical Substances MITI: Ministry of International Trade and Industry (Japan)

TSCA: Toxic Substances Control Act (USA)

Page: 24 (25)





Trade name: Marabu do it Glitter 584, 150 ml

Version: 6 / GB Date revised: 15.08.2023

Substance number: 21075006584 Replaces Version: 5 / GB Print date: 15.11.2024

VOC: Volatile Organic Compound

LD: Lethal dose

LC: Lethal concentration

SVHC: Substances of very high concern

DNEL: Derived no effect level

PNEC: Predicted no effect concentration

**UN: United Nations** 

OEL: Occupational exposure limit

#### Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: \*\*\* This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship. The information in this Safety Data Sheet is based on the present state of knowledge and current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.

Page: 25 (25)