ROYAL 🙆 TALENS

Safety data sheet according to 1907/2006/EC, Article 31 Page 1/8

Revision: 18.01.2018 Printing date 18.01.2018 SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: - ACRYLIC VARNISH MATT 115 - AMSTERDAM ACRYLIC VARNISH MATT 115 · Article number: 24285115, 24xx8115 · 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified use: Picture varnish • 1.3 Manufacturer/Supplier: Royal Talens P.O.Box 4NL-7300 AA Apeldoorn Tel. +31 (0)55 5274700 • Further information obtainable from: Regulatory Affairs safety@royaltalens.com · 1.4 Emergency telephone number: Great Britain: National Poisons Information Service (Bermingham) tel. (44) (0) 1215074123 Ireland: National Poisons Information Centre (Dublin) tel. 35 3 18379966 **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS09 environment Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects. GHS07 Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. · Hazard pictograms GHS02 GHS07 GHS09 · Signal word Warning · Hazard-determining components of labelling: Turpentine, oil Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (Contd. on page 2) GB

Printing date 18.01.2018

Revision: 18.01.2018

(Contd. of page 1)

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P271 Use only outdoors or in a well-ventilated area.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P501 Dispose of contents/container to hazardous waste collection point.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with non-hazardous additions.

• Dangerous components:		
EC/List number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	25-50%
	🚸 Flam. Liq. 3, H226; 🚸 Asp. Tox. 1, H304; 🚸 STOT SE 3, H336	
CAS: 8006-64-2	Turpentine, oil	10-25%
EINECS: 232-350-7	 Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 	
	Hydrocarbons, C9, aromatics	5-10%
Reg.nr.: 01-2119455851-35	♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H335-H336	
• Additional information: For	the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.

• After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • *After swallowing:* Do not induce vomiting; call for medical help immediately.

• 4.2 Most important symptoms and effects, both acute and delayed

Headache

May cause drowsiness or dizziness.

Nausea

Irritating to respiratory system and skin.

• 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, powder, water haze, foam
- For safety reasons unsuitable extinguishing agents: Water spray
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

GB

Printing date 18.01.2018

Revision: 18.01.2018

(Contd. of page 2)

• 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation Keep away from ignition sources.

· 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

- · 6.3 Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect from heat.

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• **Requirements to be met by storerooms and receptacles:** No special requirements.

· Information about storage in one common storage facility: Not required.

• Further information about storage conditions: Protect from heat and direct sunlight.

· Storage class: -

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

8006-64-2 Turpentine, oil (10-25%)

WEL Short-term value: 850 mg/m³, 150 ppm Long-term value: 566 mg/m³, 100 ppm

· DNFI s

·DNELS			
<i>Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics</i>			
Oral	DNEL, long term (chronic) - systemic effects	125 mg/kg bw/day (Consumer)	
Dermal	DNEL, long term (chronic) - systemic effects	125 mg/kg bw/day (Consumer)	
		208 mg/kg bw/day (Employee)	
Inhalative	DNEL, long term (chronic) - systemic effects	185 mg/m3 (Consumer)	
		871 mg/m3 (Employee)	
Hydrocarb	Hydrocarbons, C9, aromatics		
Oral	DNEL, long term (chronic) - systemic effects	11 mg/kg bw/day (Consumer)	
Dermal	DNEL, long term (chronic) - systemic effects	11 mg/kg bw/day (Consumer)	
		25 mg/kg bw/day (Employee)	
Inhalative	DNEL, long term (chronic) - systemic effects	32 mg/m3 (Consumer)	
		150 mg/m3 (Employee)	
		(Contd. on page 4)	

(Contd. on page

GB

Printing date 18.01.2018

Revision: 18.01.2018

(Contd. of page 3)

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

· Respiratory protection:

Not necessary if room is well-ventilated. Only during spraying without adequate removal by suction. **Protection of hands:**



If prolonged or repeated contact is likely, chemical resistant gloves are recommended.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material
- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye protection:



Safety glasses if risk of splashes.

9.1 Information on basic physical and ch General Information	hemical properties
Appearance:	
Form: Colour:	Fluid
Odour:	According to product specification Characteristic
Odour threshold:	Not determined.
pH-value:	Not applicable.
Change in condition Melting point/freezing point: Initial boiling point and boiling range:	Undetermined. 154-193 °C
Flash point:	24-36 °C
Flammability (solid, gas):	Not applicable.
Auto-ignition temperature:	270 °C
Decomposition temperature:	Not determined.
Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
Explosion limits:	
Lower:	0.7 Vol %
Upper:	6 Vol %
Oxidising properties	No further relevant information available.
Vapour pressure at 20 °C:	5.4 hPa
Density at 20 °C:	$0.86 g/cm^3$
Evaporation rate	Not determined.

(Contd. on page 5)

GB

Printing date 18.01.2018

Revision: 18.01.2018

	(Contd. of page
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 40 °C:	$>20.5 \text{ mm}^{2}/\text{s}$
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

• 10.1 Reactivity Dangerous reactions are not expected if the product is handled according to its intended use.

• 10.2 Chemical stability Stable under recommended storage and handling conditions (see section 7).

· 10.3 Possibility of hazardous reactions

Dangerous reactions are not expected if the product is handled according to its intended use.

· 10.4 Conditions to avoid Keep away from sources of ignition - No smoking.

• 10.5 Incompatible materials: Strong oxidising agents.

• 10.6 Hazardous decomposition products: No decomposition if used according to specifications.

SECTION 11: Toxicological information

• 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)

Inhalative LC50/4 h > 5,000 mg/l (rat)

8006-64-2 Turpentine, oil

 Oral
 LD50
 >5,000 mg/kg (rat)

 Inhalative
 LC50/4 h
 13.7 mg/l (rat)

Hydrocarbons, C9, aromatics

Oral LD50 2,000-5,000 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rabbit)

· Primary irritant effect:

· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

- Causes serious eye irritation.
- Respiratory or skin sensitisation

May cause an allergic skin reaction.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

• Germ cell mutagenicity Based on available data, the classification criteria are not met.

• *Carcinogenicity* Based on available data, the classification criteria are not met.

• Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

· Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 6)

Printing date 18.01.2018

Revision: 18.01.2018

(Contd. of page 5)

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity:

Hydrocarbons, C9, aromatics

EC50, acute 1-10 mg/l (algae)

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.

- Toxic for aquatic organisms
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name ADR	1263 PAINT RELATED MATERIAL
IMDG	ENVIRONMENTALLY HAZARDOUS PAINT RELATED MATERIAL (TURPENTINE Hydrocarbons, C9, aromatics), MARINE POLLUTANT
IATA	PAINT RELATED MATERIAL
14.3 Transport hazard class(es)	
Class	3 Flammable liquids.
Label	3

Printing date 18.01.2018

Revision: 18.01.2018

	(Contd. of page
Label	3
14.4 Packing group	
ADR, IMDĞ, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardous substance
	Turpentine, oil
Marine pollutant:	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	30
EMS Number:	F- E , S - E
Stowage Category	A
14.7 Transport in bulk according to Ann	ex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities $(\tilde{E}Q)$	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, I
-	ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.

(Contd. on page 8)

GB

Printing date 18.01.2018

Revision: 18.01.2018

	(Contd. of page 7)
H319 Causes serious eye irritation.	
H332 Harmful if inhaled.	
H335 May cause respiratory irritation.	
H336 May cause drowsiness or dizziness.	
H411 Toxic to aquatic life with long lasting effects.	
· Abbreviations and acronyms:	
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement con	ncerning the International
Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
DNEL: Derived No-Effect Level (REACH)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Liq. 3: Flammable liquids – Category 3	
Acute Tox. 4: Acute toxicity – Category 4	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
<i>Eye Irrit. 2: Serious eye damage/eye irritation – Category 2</i>	
Skin Sens. 1: Skin sensitisation – Category 1	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
Asp. Tox. 1: Aspiration hazard – Category 1	
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2	
	GB