

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

## AEROSPRAY films (varnishes), mineral spirit containing

Article No.		Issue date:	10.07.17
Version	7 ( 10.07.17 )	Page	1 / 10

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name  
50 408 - AEROSPRAY matt film (varnish)  
50 410 - AEROSPRAY neutral film (varnish)  
50 412 - AEROSPRAY gloss film (varnish)

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### General use

Products for creation of art.

##### Uses advised against

#### 1.3 Details of the supplier of the safety data sheet

H. Schmincke & Co. GmbH & Co. KG  
Otto-Hahn-Str. 2  
D - 40699 Erkrath  
Tel. +49 (0) 211-2509-0  
Fax. +49 (0) 211-2509-497  
info@schmincke.de  
www.schmincke.de

##### Dept. responsible for information

Schmincke-lab:  
mo-th 8.00-16.30, fr 8.00-13.30  
Tel. +49 (0) 211-2509-474  
labor@schmincke.de

#### 1.4 Emergency telephone number

Emergency  
Information  
Phone #

Emergencycall Berlin  
(24h - counseling in german and english)  
+49 (0) 30-30686790

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to EC regulation 1272/2008 (CLP)

Aquatic Chronic 2; H411 Toxic to aquatic life with long lasting effects.  
Eye Irrit. 2; H319 Causes serious eye irritation.  
Flam. Aerosol 1; H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
STOT RE 2; H373 May cause damage to organs through prolonged or repeated exposure.  
STOT SE 3; H335 May cause respiratory irritation.  
STOT SE 3; H336 May cause drowsiness or dizziness.

#### 2.2 Label elements

##### Labelling (CLP)



##### Signal word

Danger

##### Hazard statements

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

## AEROSPRAY films (varnishes), mineral spirit containing

Article No.		Issue date:	10.07.17
Version	7 ( 10.07.17 )	Page	2 / 10

H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.

### Safety precautions

P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe spray.  
P271 Use only outdoors or in a well-ventilated area.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P312 Call a POISON CENTER if you feel unwell.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

### 2.3 Other hazards

Repeated exposure may cause skin dryness or cracking. (EUH066)  
Contains benzotriazole derivate, alkylmethacrylate. May produce an allergic reaction. (EUH208)

## SECTION 3: Composition / information on ingredients

### 3.1 Substances

#### Chemical characterisation

acrylic resin  
white spirit  
Alcohols  
matting agents (50 408 / 50 410)  
propellant (propane / butane)  
CAS-Number  
EINECS / ELINCS / NLP  
EU index number  
Customs tariff number  
REACH registration No.  
RTECS-no.  
Hazchem-Code  
CI-Number

### 3.2 Mixtures

#### Substance 1

solvent naphtha (petroleum), light, aromatic: 25 - 50 %  
CAS: 64742-95-6  
REACH: 01-2119455851-35  
Aquatic Chronic 2; H411 / Asp. Tox. 1; H304 / Flam. Liq. 3; H226 / STOT SE 3; H335 / STOT SE 3; H336 / EUH066

#### Substance 3

naphtha (petroleum), hydrotreated light: 0 - < 10 %  
CAS: 64742-49-0  
Aquatic Chronic 2; H411 / Asp. Tox. 1; H304 / Flam. Liq. 2; H225 / STOT SE 3; H336 / EUH066

#### Substance 2

naphtha (petroleum), hydrodesulphurized heavy: 3 - < 10 %  
CAS: 64742-82-1  
REACH: 01-2119458049-33-xxxx  
Aquatic Chronic 2; H411 / Asp. Tox. 1; H304 / Flam. Liq. 3; H226 / STOT RE 1; H372 / STOT SE 3; H336 / EUH066

#### Substance 4

butan-1-ol: 1 - < 3 %  
CAS: 71-36-3  
REACH: 01-2119484630-38-xxxx  
Acute Tox. 4; H302 / Eye Dam. 1; H318 / Flam. Liq. 3;

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

## AEROSPRAY films (varnishes), mineral spirit containing

Article No.		Issue date:	10.07.17
Version	7 ( 10.07.17 )	Page	3 / 10

H226 / STOT SE 3; H335 / STOT SE 3; H336 / Skin Irrit. 2; H315

### Substance 5

ethanol: 0 - < 2 %  
CAS: 64-17-5  
REACH: 01-2119457610-43-XXXX  
Eye Irrit. 2; H319 / Flam. Liq. 2; H225

### Substance 7

alkylmethacrylate: 0,1 - < 1,0 %  
CAS: 97-88-1  
Eye Irrit. 2; H319 / Flam. Liq. 3; H226 / STOT SE 3;  
H335 / Skin Irrit. 2; H315 / Skin Sens. 1; H317

### Substance 9

propane: 1 - 10 %  
CAS: 74-98-6  
REACH: 01-2119471330-49  
Compr. Gas; H280 / Flam. Gas 1; H220

### Substance 6

derivate of Benzotriazol: 0,1 - < 1,0 %  
CAS: 104810-47-1  
Aquatic Chronic 2; H411 / Skin Sens. 1; H317

### Substance 8

butane: 20 - 30 %  
CAS: 106-97-8  
REACH: 01-2119474691-32  
Compr. Gas; H280 / Flam. Gas 1; H220

### Additional information

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

#### In case of inhalation

Move victim to fresh air, put at rest and loosen restrictive clothing. Seek medical attention if problems persist.

#### In case of skin contact

Thoroughly wash skin with soap and water. Seek medical attention if irritation persists.

#### After eye contact

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart.  
Subsequently consult an ophthalmologist.

#### After swallowing

Call a POISON CENTER/doctor if you feel unwell.

### 4.2 Most important symptoms and effects, both acute and delayed

### 4.3 Indication of any immediate medical attention and special treatment needed

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

extinguishing powder carbon dioxide Water fog

#### Extinguishing media which must not be used for safety reasons

### 5.2 Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide and carbon dioxide

### 5.3 Advice for firefighters

#### Special protective equipment for firefighters

Use appropriate respiratory protection.

#### Additional information

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

## AEROSPRAY films (varnishes), mineral spirit containing

Article No.

Version

7 ( 10.07.17 )

Issue date:

Page

10.07.17

4 / 10

refer to section 8

### 6.2 environmental precautions

Do not allow to enter into surface water or drains.

### 6.3 Methods and material for containment and cleaning up

#### Methods for cleaning up

Absorb leftover product with non-flammable liquid-binding material (e.g. earth, sand, vermiculite or ground sand stone) and place in closed containers for disposal.

#### Additional information

### 6.4 Reference to other sections

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Advices on safe handling

Provide good ventilation and/or an exhaust system in the work area. In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

#### Precautions against fire and explosion

### 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements for storerooms and containers

Store in a well-ventilated place. Keep container tightly closed. Keep away from sources of ignition and heat. Protect from direct sunlight.

#### Hints on joint storage

#### Storage class

#### Further details

### 7.3 Specific end use(s)

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

64742-95-6 solvent naphtha (petroleum), light, aromatic

DEU	WEL	100,000	mg/m <sup>3</sup>	TRGS 900
-----	-----	---------	-------------------	----------

71-36-3 butan-1-ol

DEU	WEL	100,000	mL/m <sup>3</sup>	1(I); DFG, Y
DEU	WEL	310,000	mg/m <sup>3</sup>	1(I); DFG, Y

64-17-5 ethanol

DEU	WEL	500,000	mL/m <sup>3</sup>	-
DEU	WEL	960,000	mg/m <sup>3</sup>	2(II); DGF; Y
USA	PEL (US)	1.000,000	ppm	8h (long term)
USA	PEL (US)	1.900,000	mg/m <sup>3</sup>	8h (long term)

106-97-8 butane

DEU	WEL	1.000,000	mL/m <sup>3</sup>	-
DEU	WEL	2.400,000	mg/m <sup>3</sup>	4(II); DGF

74-98-6 propane

DEU	WEL	1.000,000	mL/m <sup>3</sup>	-
DEU	WEL	1.800,000	mg/m <sup>3</sup>	4(II); DFG

### 8.2 Exposure controls

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

## AEROSPRAY films (varnishes), mineral spirit containing

Article No.		Issue date:	10.07.17
Version	7 ( 10.07.17 )	Page	5 / 10

### Occupational exposure controls

#### Respiratory protection

Respiratory protection must be worn whenever the WEL levels have been exceeded.  
Combination filtering device (EN 14387) Use filter type A (= against vapours of organic substances)

#### Hand protection

Qualified materials: Nitrile rubber  
Layer thickness > 0,35 mm  
Breakthrough time > 480 min  
Ultranitril 492 - MAPA GmbH, Industriestraße 21- 25, D-27404 Zeven, Internet: [www.mapa-pro.de](http://www.mapa-pro.de)  
All information was derived in accordance with EU directive 89/686/EEG and the resultant EN 374 in cooperation with MAPA GmbH. This recommendation applies exclusively to the product and use named in Section 1. In the event of commingling or deviating conditions, contact the suppliers of CE-approved gloves.  
This information is based on our current state of knowledge and describes the security standards applicable to our product for the purpose provided.

#### Eye protection

Goggles

#### Body protection

Wash contaminated clothing prior to re-use.

#### General protection and hygiene measures

Handle in accordance with good industrial hygiene and safety practice. After work, wash hands and face.

## SECTION 9: Physical and chemical properties

### 9.1 information on basic physical and chemical properties

Form	Aerosol		
Colour	colourless		
Odour	characteristic		
		min	max
Initial boiling point and boiling range			
Melting point/freezing point			
Flash point/flash point range		-60 °C	-60 °C
Flammability			
Ignition temperature			
Auto-ignition temperature			
Explosion limits		0,6	8,5 Vol%
Refraction index			
Partition coefficient: n-octanol/water			
Danger of explosion			
Vapour pressure		300 kPa	
Density		~	
		0,71 g/ml	
PH value			
Viscosity dynamic of			
Viscosity dynamic up to			
Viscosity kinematic of			
Viscosity kinematic up to			

### 9.2 Other information

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

### 10.2 Chemical stability

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

## AEROSPRAY films (varnishes), mineral spirit containing

Article No.		Issue date:	10.07.17
Version	7 ( 10.07.17 )	Page	6 / 10

### 10.3 Possibility of hazardous reactions

### 10.4 Conditions to avoid

Protect from heat and direct sunlight.

### 10.5 Incompatible materials

Oxidising agent

### 10.6 Hazardous decomposition products

64742-95-6 solvent naphtha (petroleum), light, aromatic

oral	LD50	Rat	>	2000,000	mg/kg	-
dermal	LD50	Rat	>	2000,000	mg/kg	-

64742-82-1 naphtha (petroleum), hydrodesulphurized heavy

oral	LD50	Rat	>	2000,000	mg/kg	-
dermal	LD50	Rat	>	2000,000	mg/kg	-

71-36-3 butan-1-ol

oral	LD50	Rat		790,000	mg/kg	-
inhalative	LC50	Rat		8000,000	mg/l	(4h)
dermal	LD50	Rabbit	>	3400,000	mg/kg	-

64-17-5 ethanol

oral	LD50	Rat		5000,000	mg/kg	-
inhalative	LC50	Rat	>	1800,000	mg/l	4h
dermal	LD50	Rabbit	>	10000,000	mg/kg	-

97-88-1 alkylmethacrylate

oral	LD50	Rat		16000,000	mg/kg	-
dermal	LD50	Rabbit	>	10100,000	mg/kg	-

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

No data available

#### In case of inhalation

May cause respiratory irritation.

#### After swallowing

No data available

#### In case of skin contact

No data available

#### After eye contact

Causes serious eye irritation.

### Practical experience

### General remarks

### Toxicological tests

64742-95-6 solvent naphtha (petroleum), light, aromatic

LC50	fish	>	10,000	mg/l	-
LC50	Algae	>	10,000	mg/l	-

64742-82-1 naphtha (petroleum), hydrodesulphurized heavy

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

## AEROSPRAY films (varnishes), mineral spirit containing

Article No.		Issue date:	10.07.17
Version	7 ( 10.07.17 )	Page	7 / 10

71-36-3	butan-1-ol	LC50	fish	>	10,000	mg/l	-
		EC50	Algae	>	10,000	mg/l	-
64-17-5	ethanol	EC50	Daphnia magna (Big water		1983,000	mg/l	(48h)
		IC50:	Algae	>	500,000	mg/l	(72h)
		LC50	fish		8150,000	mg/l	48h
		EC50	Daphnia magna	>	14221,000	mg/l	48h

## SECTION 12: Ecological information

### 12.1 Toxicity

Aquatic toxicity

Water Hazard Class

2

WGK catalog number

General information

### 12.2 Persistence and degradability

Further details

Oxygen demand

### 12.3 Bioaccumulative potential

Bioconcentration factor (BCF)

Partition coefficient: n-octanol/water

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

No data available

### 12.6 Other adverse effects

General information

### Ecotoxicological effects

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

Waste key number

160504

160504\* Gases in pressure containers (including halons) containing dangerous substances.

Recommendation

#### Contaminated packaging

Waste key number

Recommendation

Completely emptied packages can be recycled.

#### Additional information

## SECTION 14: Transport information

### 14.1 UN number

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

## AEROSPRAY films (varnishes), mineral spirit containing

Article No.		Issue date:	10.07.17
Version	7 ( 10.07.17 )	Page	8 / 10

1950

### 14.2 UN proper shipping name

ADR, ADN	AEROSOLS, flammable
IMDG, IATA	AEROSOLS, flammable

### 14.3 Transport hazard class(es)

ADR, ADN	2
IMDG	2.1
IATA	2.1

### 14.4 Packing group

-

### 14.5 Environmental hazards

Marine Pollutant - IMDG	Yes
Marine Pollutant - ADN	

### 14.6 Special precautions for user

#### Land transport

Code: ADR/RID	5F
Kemmler-number	-
Hazard label ADR	2.1
Limited quantities	1L
Contaminated packaging: Instructions	P207 - LP200
Contaminated packaging: Special provisions	PP87 - RR6 - L2
Special provisions for packing together	MP9
Portable tanks: Instructions	-
Portable tanks: Special provisions	-
Tank coding	-
Tunnel restriction	D
Remarks	
EQ	E0
Special provisions	190 - 327 - 344 - 625

#### Inland waterway craft

Hazard label
Limited quantities
Transport permitted
Equipment necessary
Ventilation
Remarks
EQ
Special provisions

#### Sea transport

EmS	F-D, S-U
Special provisions	63 - 190 - 277 - 327 - 344 - 381 - 959
Limited quantities	1L
Contaminated packaging: Instructions	P207 - LP200
Contaminated packaging: Special provisions	PP87 - L2
IBC: Instructions	-
IBC: Provisions	-
Tank instructions IMO	-
Tank instructions UN	-
Tank instructions Special provisions	-



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

## AEROSPRAY films (varnishes), mineral spirit containing

Article No.		Issue date:	10.07.17
Version	7 ( 10.07.17 )	Page	9 / 10

Stowage and segregation category A  
SW1 - SG69

### Properties and observations

#### Remarks

EQ E0

### Air transport

Hazard -  
Passenger 203 (75 kg)  
Passenger LQ Y203 (30 kg G)  
Cargo 203 (150 kg)  
ERG 10L  
Remarks  
EQ  
Special Provisioning A145 - A167 - A802

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### National regulations

##### Europe

Contents of VOC [%] 0  
Contents of VOC  
[g/L]  
Further regulations, limitations and legal requirements

##### Germany

Storage class  
Water Hazard Class 2  
WGK catalog number  
Incident regulation  
Information on working limitations  
Further regulations, limitations and legal requirements

##### Denmark

Further regulations, limitations and legal requirements

##### Hungary

Further regulations, limitations and legal requirements

##### Great Britain

Further regulations, limitations and legal requirements

##### Switzerland

Contents of VOC [%]  
~ 87 %  
Further regulations, limitations and legal requirements

##### USA

Further regulations, limitations and legal requirements  
Federal Regulations

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

## AEROSPRAY films (varnishes), mineral spirit containing

Article No.		Issue date:	10.07.17
Version	7 ( 10.07.17 )	Page	10 / 10

### State Regulations

#### Japan

Further regulations, limitations and legal requirements

#### Canada

Further regulations, limitations and legal requirements

### 15.2 Chemical Safety Assessment

## SECTION 16: Other information

### Further information

Hazard statements (CLP)	H220 Extremely flammable gas. H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H229 Pressurised container: May burst if heated. H280 Contains gas under pressure; may explode if heated. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H372 Causes damage to organs through prolonged or repeated exposure. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.
-------------------------	---

### Further information

This information is abased on our current state of knowledge and describes the security standards applicable to our product for the purpose provided. The information provided here does not constitute a legally binding warranty of specific characteristics or of suitability for a specific application use of the product is thus to be adapted to the user's special conditions and checked by preliminary tests. We are thus unable to guarantee product characteristics or accept an liability for damage arising in connection with the use of our products.

### Literature

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

### Reason of change

### Additional information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.