

Printing date 25.01.2017 Version number 1 Revision: 02.12.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier

- Trade name: Kövulfix Rekord

- Article number: R054141-01

- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- Application of the substance / the mixture Adhesives

- 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier:

Kömmerling Chemische Fabrik GmbH Zweibrücker Straße 200 D-66954 Pirmasens Tel.: +49 (0)6331/56-2000 www.koe-chemie.de

- Informing department:

Abteilung: C-U Qualitäts- und Umweltmanagementcenter

(department: C-U Quality- and Environmentalmanagementcenter)

Tel.: +49 (0)6331/56-2553; Fax.: +49 (0)6331/56-1091

e-Mail: Productsafety@Koe-Chemie.de

- 1.4 Emergency telephone number:

In case of poisoning: GBK-EMTEL International

Tel.(24h): +49(0)6132/84463 (all languages)

In case of transport accidents:

Tel.(24h): (001) 352 323 3500 (Infotrac - Contract ID: 90373 / GBK)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- Additional information: The classification resulted from the calculation method of CLP-regulation.

- 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms





GHS02 GHS07

- Signal word Danger

(Contd. on page 2)

Printing date 25.01.2017 Version number 1 Revision: 02.12.2014

Trade name: Kövulfix Rekord

(Contd. of page 1)

- Hazard-determining components of labelling:

butanone

hydrocarbons, C6-C7

acetone

- Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P243 Take precautionary measures against static discharge.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention. P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

- Additional information:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

EUH208 Contains rosin. May produce an allergic reaction.

This product is not to be used under

conditions of poor ventilation.

This product is not to be used for carpet

laying.

- 2.3 Other hazards

In the event of a large-scale use of the product, ignition sources in the immediate proximity and in low-lying areas, such as welding equipment, bells, heating elements, refrigerators, storage heaters etc. should be switched off! Erect warning signs warning of the hazardous risk of explosive atmosphere!

- Results of PBT and vPvB assessment

- PBT: Not applicable.

- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Chemical characterisation: Mixtures

- Description: Mixture of several substances

- Dangerous components:		
CAS: 78-93-3	butanone	20-<40%
EINECS: 201-159-0	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3,	
Reg.nr.: 01-2119457290-43-xxxx	H336	
EC number: 921-024-6	hydrocarbons, C6-C7	15-25%
Reg.nr.: 01-2119475514-35-xxxx	Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	

(Contd. on page 3)



Printing date 25.01.2017 Version number 1 Revision: 02.12.2014

Trade name: Kövulfix Rekord

	(C	ontd. of page 2)
CAS: 67-64-1	acetone	10-20%
EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	- 1
CAS: 8050-09-7 EINECS: 232-475-7	rosin Skin Sens. 1, H317	< 1.0%

- SVHC Doesn't contain SVHC-substances
- Additional information

EC-number 921-024-6: Outside of Europe this substance is assigned CAS-Nr. 64742-49-0 (naphtha [petroleum], hydrotreated light);

Mixture of isoalkanes, n-alkanes, cyclenes (Content of benzene [CAS-Nr.: 71-43-2] < 0,1%, cyclohexane [CAS-Nr.: 110-82-7] < 25%, n-hexane [110-54-3] < 5%)

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- After inhalation

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness bring patient into a stable side position for transport.

- After skin contact

Treat affected skin with cotton wool or cellulose. Then wash and rinse thoroughly with water and a mild cleaning agent.

- After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.
- After swallowing Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents

Water spray

Alcohol-resistant foam

Fire-extinguishing powder

Carbon dioxide

- For safety reasons unsuitable extinguishing agents Water with full jet.
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- **Protective equipment:** Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

Use respiratory protective device against the effects of fumes/dust/aerosol.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Pick up mechanically.

(Contd. on page 4)



Printing date 25.01.2017 Version number 1 Revision: 02.12.2014

Trade name: Kövulfix Rekord

(Contd. of page 3)

- 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.

- 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.
- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:

Protect from frost.

Keep receptacle tightly sealed.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

Store in dry conditions.

- Storage class (according german VCI-concept): 3
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- 8.1 Control parameters

- Components with limit values that require monitoring at the workplace:			
78-93-3 butanone			
WEL (Great Britain)	Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, BMGV		
IOELV (European Union)	Short-term value: 900 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm		
67-64-1 acetone			
WEL (Great Britain)	Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm		
IOELV (European Union)	Long-term value: 1210 mg/m³, 500 ppm		
8050-09-7 rosin			
WEL (Great Britain)	Short-term value: 0.15 mg/m³ Long-term value: 0.05 mg/m³ Sen		
- DNELs			
hydrocarbons, C6-C7			
Inhalative worker (long-te	erm exposure/systemic) 3.25 mg/m³		

(Contd. on page 5)

Printing date 25.01.2017 Version number 1 Revision: 02.12.2014

Trade name: Kövulfix Rekord

(Contd. of page 4)

- Ingredients with biological limit values:

78-93-3 butanone

BMGV (Great Britain) 70 µmol/L

Medium: urine

Sampling time: post shift Parameter: butan-2-one

- Additional information:

The homogeneous mixing of this product is guaranteed through continuous physical tests. What were formerly dusty raw materials are completely integrated into the liquid/pasty mass. Potential threshold limit values (maximum concentration values at the workplace) of solid substances are therefore not named, because the risk of inhalation of these substances (during handling of this mixture) is not anymore given.

- 8.2 Exposure controls

- Personal protective equipment

- General protective and hygienic measures

The usual precautionary measures should be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of the work.

Immediately remove all soiled and contaminated clothing

- Breathing equipment:

Not required with good ventilation and/or adequate extractor facilities

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Short term filter device:

Filter AX (DIN EN 371 [DIN EN 141])

- Protection of hands:

Direct contact with the chemical preparation must be avoided by organizational measures. Apply skin protectant before working with gloves to avoid skin swellings and use a skin cleansing and skincare product after the work.

Compliance with the stated penetration time (starts with the first product contact) must be ensured! The gloves need to be disposed of after the penetration time and new gloves used!

- For the permanent contact gloves made of the following materials are suitable:

If longer exposure to the chemical preparation is necessary, a sturdy overglove against mechanical strain is recommended in combination with the "Barrier 02-100" underglove from Ansell (penetration time 480 min).

- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber (0.7mm - penetration time 15 min)

- As protection from splashes gloves made of the following materials are suitable:

Recommended for protection from splashes: disposable nitrile gloves (minimum thickness 0.12 mm) with long cuffs. After contact with the chemical preparation, take the disposable nitrile glove off immediately and put on a new disposable nitrile glove.

- Eye protection: Safety glasses

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- General Information
- Appearance:

Form: Fluid

Colour: Amber coloured

(Contd. on page 6)



Printing date 25.01.2017 Version number 1 Revision: 02.12.2014

Trade name: Kövulfix Rekord

	(Contd. of page
- Odour:	Solvent-like
- Odour threshold:	Not determined.
- Change in condition Initial boiling point and boiling range	e: 56 °C
- Flash point:	-17 °C
- Ignition temperature:	> 200 °C
- Explosion limits:	
Lower:	0.6 Vol %
Upper:	13 Vol %
- Vapour pressure at 20 °C:	240 hPa
- Specific gravity at 20 °C:	0.83 g/cm ³
- Vapour density	Not determined.
- Evaporation rate	Not determined.
- Solubility in / Miscibility with	
Water:	Partly soluble
- Partition coefficient: n-octanol/water:	Not determined.
- Viscosity:	
dynamic at 20 °C:	1600 mPas (Brookfield)
- Solvent content:	
Organic solvents:	75.9 %
VOC (EU):	629.5 g/l
VOC (EU):	75.85 %
VOC (CH):	75.85 %
- 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions Reacts with oxidizing agents
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

In case of fire, the following substance(s) may occur:

Hydrogen chloride (HCI)

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- Primary irritant effect:
- Skin corrosion/irritation

Causes skin irritation.

(Contd. on page 7)

Printing date 25.01.2017 Version number 1 Revision: 02.12.2014

Trade name: Kövulfix Rekord

(Contd. of page 6)

- Serious eye damage/irritation Causes serious eye irritation.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity:

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes: Do not allow product to reach ground water, water course or sewage system.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation Disposal in accordance with official regulations
- EWC-Code(s):

To be treated as industrial waste: do not dispose of in or on soil, in watercourses or bodies, or through a sewage system. These EU refuse code numbers are recommendations for waste accruing through the use of adhesives and sealants. Any waste produced from organic solvents or other dangerous substances listed under item 3 of this safety datasheet is itself classified as dangerous (*).

Waste accruing during application:

080409* waste adhesives and sealants containing organic solvents or other dangerous substances 080410 waste adhesives and sealants other than those mentioned in 080409

Waste accruing during cleaning:

08 04 11* adhesive and sealant sludges containing organic solvents or other dangerous substances 08 04 12 adhesive and sealant sludges other than those mentioned in 080411

Soiled waste packaging:

15 01 10* packaging containing residues of or contaminated by dangerous substances.

Clean waste packaging:

15 01 01 paper and cardboard packaging

15 01 02 plastic packaging

15 01 04 metallic packaging

(Contd. on page 8)



Printing date 25.01.2017 Version number 1 Revision: 02.12.2014

Trade name: Kövulfix Rekord

- Uncleaned packagings:

(Contd. of page 7)

- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport informa	tion
- 14.1 UN-Number - ADR/RID/ADN, IMDG, IATA	UN1133
14.2 UN proper shipping nameADR/RID/ADNIMDGIATA	1133 ADHESIVES ADHESIVES (hydrocarbons, C6-C7, ACETONE) ADHESIVES
- 14.3 Transport hazard class(es)	
- ADR/RID/ADN, IMDG, IATA	
- Class - Label	3 Flammable liquids. 3
- 14.4 Packing group - ADR/RID/ADN - IMDG, IATA	
14.5 Environmental hazards:Marine pollutant:	- No
- 14.6 Special precautions for user- Danger code (Kemler):- EMS Number:- Stowage Category	Warning: Flammable liquids. 33 F-E,S-D B
- 14.7 Transport in bulk according to An Marpol and the IBC Code	nex II of Not applicable.
- Transport/Additional information:	
- ADR/RID/ADN - Limited quantities (LQ) - Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
- Transport category - Tunnel restriction code	3 D/E
- IMDG - Limited quantities (LQ)	5L



Printing date 25.01.2017 Version number 1 Revision: 02.12.2014

Trade name: Kövulfix Rekord

	(Contd. of page 8
- Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
- Remarks:	(Packing group III, if content of packaging \leq 30l according 2.3.2.2 IMDG)
- IATA	
- Remarks:	(Packing group III, if content of packaging \leq 30I according 3.3.3.1.1 IATA)
- UN "Model Regulation":	UN 1133 ADHESIVES, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 48
- National regulations
- Information about limitation of use:

Employment restrictions concerning young persons must be observed.

- Disturbance regulations:

Critical quantity values according to the regulations on accidents should be adhered to.

- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

For industrial use only.

- Legend of H- and R-phrases, concerning the in chapter 3 mentioned substances (marking of product please see chapter 2)

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

- Department issuing SDS:

- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

(Contd. on page 10)



Printing date 25.01.2017 Version number 1 Revision: 02.12.2014

Trade name: Kövulfix Rekord

(Contd. of page 9)

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic

compounds)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH) PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

GB