Safety data sheet
according to UK REACH

Printing date 10.12.2025 *Version number 6.0 (replaces version 5.9)* *Revision: 10.12.2025*

*
SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Sprühkleber permanent

Article number: 100062/1
1.2 Relevant identified uses of the substance or mixture and uses advised against
Sector of Use SU21 Consumer uses: Private households / general public / consumers
Application of the substance / the mixture Adhesives

1.3 Details of the supplier of the safety data sheet
Manufacturer/Supplier:
Stanger Produktions- und Vertriebs GmbH
Ferdinand-Porsche-Straße 2
D-32339 Espelkamp
Telefon: +49 5743-9307-0

Further information obtainable from:
Product Safety Department
info@stanger.de

1.4 Emergency telephone number:
+49-5743-9307-0
Monday to Friday, 7:00 a.m. to 5:00 p.m.

*
SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
Classification according to Regulation (EC) No 1272/2008

Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
Skin Irrit. 2	H315	Causes skin irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.

2.2 Label elements
Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the GB CLP regulation.
GHS label elements
The product is classified and labelled according to the GB CLP regulation.
Hazard pictograms



GHS02 GHS07 GHS09

Signal word Danger

Hazard-determining components of labelling:
hexane (containing < 5 % n-hexane (203-777-6))
cyclohexane
Hazard statements
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
Precautionary statements
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.

(Contd. on page 2)

Safety data sheet
according to UK REACH

Printing date 10.12.2025 Version number 6.0 (replaces version 5.9) Revision: 10.12.2025

Trade name: Sprühkleber permanent

(Contd. of page 1)

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
Additional information:
Buildup of explosive mixtures possible without sufficient ventilation.
2.3 Other hazards
Results of PBT and vPvB assessment Not applicable.
PBT: Not applicable.
vPvB: Not applicable.

*
SECTION 3: Composition/information on ingredients

3.2 Mixtures
Description:
Mixture of substances listed below with nonhazardous additions.
Active substance with propellant

Dangerous components:		
CAS: 107-83-5 EINECS: 203-523-4 Reg.nr.: 01-2119484651-34	hexane (containing < 5 % n-hexane (203-777-6)) Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336 Note: C	25-75%
CAS: 110-82-7 EINECS: 203-806-2 Reg.nr.: 01-2119463273-41	cyclohexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336	≥0.25-<2.5%

Additional information: For the wording of the listed hazard phrases refer to section 16.

*
SECTION 4: First aid measures

4.1 Description of first aid measures
After inhalation: In case of unconsciousness place patient stably in side position for transportation.
After skin contact: Immediately wash with water and soap and rinse thoroughly.
After eye contact: Rinse opened eye for several minutes under running water.
4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

*
SECTION 5: Firefighting measures

5.1 Extinguishing media
Suitable extinguishing agents:
CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
5.2 Special hazards arising from the substance or mixture No further relevant information available.
5.3 Advice for firefighters
Protective equipment: Wear self-contained respiratory protective device.

*
SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
6.2 Environmental precautions:
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

Safety data sheet
according to UK REACH

(Contd. of page 2)

6.3 Methods and material for containment and cleaning up:
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
No special measures required.
6.4 Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

*
SECTION 7: Handling and storage

7.1 Precautions for safe handling *Ensure good ventilation/exhaustion at the workplace.*
Information about fire - and explosion protection:
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

7.2 Conditions for safe storage, including any incompatibilities
Storage:
Requirements to be met by storerooms and receptacles:
Observe official regulations on storing packagings with pressurised containers.
Information about storage in one common storage facility: *Not required.*
Further information about storage conditions: *Keep container tightly sealed.*
Storage class: *2 B*
7.3 Specific end use(s) *No further relevant information available.*

*
SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:	
110-82-7 cyclohexane	
WEL	*Short-term value: 1050 mg/m³, 300 ppm* *Long-term value: 350 mg/m³, 100 ppm*

Additional information: *The lists valid during the making were used as basis.*

8.2 Exposure controls
Appropriate engineering controls *No further data; see section 7.*
Individual protection measures, such as personal protective equipment
General protective and hygienic measures:
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Respiratory protection: *Not required.*
Hand protection
Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
Material of gloves
Butyl rubber, BR
Nitrile rubber, NBR
Recommended thickness of the material: ≥ 0.35-0.5 mm
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the

(Contd. on page 4)

Safety data sheet
according to UK REACH

(Contd. of page 3)

resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

Butyl rubber, BR
Nitrile rubber, NBR

For the permanent contact gloves made of the following materials are suitable: *Butyl rubber, BR*

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Nitrile rubber, NBR
Chloroprene rubber, CR

Eye/face protection *Not required.*

*

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information	
Physical state	*Aerosol*
Colour:	*Yellowish*
Odour:	*Characteristic*
Boiling point or initial boiling point and boiling range	*<0 °C* *Not applicable, as aerosol.*
Lower and upper explosion limit	
Lower:	*1.4 Vol %*
Upper:	*10.9 Vol %*
Flash point:	*-97 °C*
Auto-ignition temperature:	*285 °C*
pH	*Mixture is non-polar/aprotic.*
Solubility	
water:	*Not miscible or difficult to mix.*
Partition coefficient n-octanol/water (log value)	*Not determined.*
Vapour pressure at 20 °C:	*8,300 hPa*
Density and/or relative density	
Density at 20 °C:	*0.64 g/cm³*

9.2 Other information	*No further relevant information available.*
Appearance:	
Form:	*Aerosol*
Important information on protection of health and environment, and on safety.	
Ignition temperature:	*Product is not selfigniting.*
Explosive properties:	*Product is not explosive. However, formation of explosive air/vapour mixtures are possible.*
Solvent separation test:	
Organic solvents:	*70.0 %*
VOC (EC)	*543.0 g/l*

Information with regard to physical hazard classes	
Explosives	*Void*
Flammable gases	*Void*
Aerosols	*Extremely flammable aerosol. Pressurised container: May burst if heated.*
Oxidising gases	*Void*
Gases under pressure	*Void*

(Contd. on page 5)

Safety data sheet
according to UK REACH

Trade name: Sprühkleber permanent

(Contd. of page 4)

Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

*
SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.
10.2 Chemical stability
Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
10.3 Possibility of hazardous reactions No dangerous reactions known.
10.4 Conditions to avoid No further relevant information available.
10.5 Incompatible materials: No further relevant information available.
10.6 Hazardous decomposition products: No dangerous decomposition products known.

*
SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:		
110-82-7 cyclohexane		
Oral	LD50	12,705 mg/kg (rat)

Primary irritant effect:
Skin corrosion/irritation Causes skin irritation.
STOT-single exposure May cause drowsiness or dizziness.
Aspiration hazard May be fatal if swallowed and enters airways.
11.2 Information on other hazards

Endocrine disrupting properties
None of the ingredients is listed.

*
SECTION 12: Ecological information

12.1 Toxicity
Aquatic toxicity: No further relevant information available.
12.2 Persistence and degradability No further relevant information available.
12.3 Bioaccumulative potential No further relevant information available.
12.4 Mobility in soil No further relevant information available.
12.5 Results of PBT and vPvB assessment Not applicable.
12.6 Endocrine disrupting properties
The product does not contain substances with endocrine disrupting properties.
12.7 Other adverse effects No further relevant information available.
Remark: Toxic for fish

(Contd. on page 6)

Safety data sheet
according to UK REACH

Trade name: Sprühkleber permanent

(Contd. of page 5)

Additional ecological information:
General notes:
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.

*
SECTION 13: Disposal considerations

13.1 Waste treatment methods
Recommendation
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:
Recommendation: *Disposal must be made according to official regulations.*

*
SECTION 14: Transport information

14.1 UN number or ID number	
ADR, IMDG, IATA	*UN1950*
14.2 UN proper shipping name	
ADR	*UN1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS*
IMDG	*AEROSOLS, MARINE POLLUTANT*
IATA	*AEROSOLS, flammable*
14.3 Transport hazard class(es)	
ADR	



Class	*2 5F Gases.*
Label	*2.1*
IMDG	



Class	*2.1 Gases.*
Label	*2.1*
IATA	



Class	*2.1 Gases.*
Label	*2.1*
14.4 Packing group	
ADR, IMDG, IATA	*Void*

(Contd. on page 7)

Safety data sheet
according to UK REACH

Trade name: Sprühkleber permanent

(Contd. of page 6)

14.5 Environmental hazards:	Product contains environmentally hazardous substances: hexane (containing < 5 % n-hexane (203-777-6))
Marine pollutant:	Yes Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Gases.
Hazard identification number (Kemler code):	-
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

*

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
Poisons Act

Regulated explosives precursors
None of the ingredients is listed.

Regulated poisons
None of the ingredients is listed.

Reportable explosives precursors
None of the ingredients is listed.

Reportable poisons
None of the ingredients is listed.

(Contd. on page 8)

Safety data sheet
according to UK REACH

Trade name: Sprühkleber permanent

(Contd. of page 7)

Directive 2012/18/EU
Named dangerous substances - ANNEX I *None of the ingredients is listed.*
Seveso category
P3a FLAMMABLE AEROSOLS
E2 Hazardous to the Aquatic Environment
Qualifying quantity (tonnes) for the application of lower-tier requirements *150 t*
Qualifying quantity (tonnes) for the application of upper-tier requirements *500 t*
15.2 Chemical safety assessment: *A Chemical Safety Assessment has not been carried out.*

*
SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases
H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

Department issuing SDS: *Product Safety Department*
Contact: *Stanger Produktion und Vertrieb GmbH*
Abbreviations and acronyms:
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Aerosol 1: Aerosols – Category 1
Flam. Liq. 2: Flammable liquids – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
**** Data compared to the previous version altered.***