

Printing date 27.01.2015 Revision: 27.01.2015

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: COBRA VARNISH GLOSS ODOURLESS 102, aerosol

· Article number: 9516.3102

· 1.2 Relevant identified uses of the substance or mixture picturevarnish

· 1.3 Manufacturer/Supplier:

Royal Talens P.O.Box 4

NL-7300 AA Apeldoorn Tel. +31 (0)55 5274700

· Further information obtainable from:

Regulatory Affairs safety@talens.com

· 1.4 Emergency telephone number:

Great Britain: National Poisons Information Service (Bermingham) tel. (44) (0) 1215074123

Ireland: National Poisons Information Centre (Dublin) tel. 35 3 18379966

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Aquatic Chronic 4 H413 May cause long lasting harmful effects to aquatic life.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



F+; Extremely flammable

R12: Extremely flammable.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurised container.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS02

- · Signal word Danger
- · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H413 May cause long lasting harmful effects to aquatic life.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

*P251* Do not pierce or burn, even after use.

*P260* Do not breathe spray.

(Contd. on page 2)



Printing date 27.01.2015 Revision: 27.01.2015

(Contd. of page 1)

*P211* Do not spray on an open flame or other ignition source.

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

*P501* Dispose of contents/container to hazardous waste collection point.

 $\cdot$  Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

#### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64741-65-7	Naphtha (petroleum), heavy alkylate	25-50%
EINECS: 265-067-2	<b>X</b> Xn R65	
Reg.nr.: 01-2119472146-39	R53-66	
-	🏇 Flam. Liq. 3, H226; 🚯 Asp. Tox. 1, H304; Aquatic Chronic 4, H413	
CAS: 106-97-8	butane	10-25%
EINECS: 203-448-7	<b>▶</b> F+ R12	
Reg.nr.: 01-2119474691-32	🏵 Flam. Gas 1, H220; Press. Gas C, H280	
CAS: 74-98-6	propane	10-25%
EINECS: 200-827-9	F+ R12	
Reg.nr.: 01-2119486944-21	🔖 Flam. Gas 1, H220; Press. Gas C, H280	

<sup>·</sup> Additional information: For the wording of the listed risk phrases refer to section 16.

### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; call for medical help immediately.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, powder, water haze, foam
- · For safety reasons unsuitable extinguishing agents:

Water

Water with full jet

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Keep away from ignition sources.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)



Printing date 27.01.2015 Revision: 27.01.2015

(Contd. of page 2)

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Open and handle receptacle with care.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

### SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

#### 106-97-8 butane

WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.
- · Protection of hands:



If prolonged or repeated contact is likely, chemical resistant gloves are recommended.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)

(Contd. of page 3)



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.01.2015 Revision: 27.01.2015

· Eye protection:



### SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Aerosol

Colour: According to product specification

· Odour: Characteristic

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: -44 °C

· Flash point: -97 °C

• Ignition temperature: 365 °C

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapour

mixtures are possible.

· Explosion limits:

 Lower:
 0.7 Vol %

 Upper:
 10.9 Vol %

· Vapour pressure at 20 °C: 8300 hPa

• Density at 20 °C:  $0.68 \text{ g/cm}^3$ 

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

• 9.2 Other information No further relevant information available.

#### SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values relevant for classification:

#### 64741-65-7 Naphtha (petroleum), heavy alkylate

 Oral
 LD50
 > 5000 mg/kg (rat)

 Dermal
 LD50
 > 5000 mg/kg (rabbit)

 Inhalative
 LC50/4 h
 > 5 mg/l (rat)

(Contd. on page 5)



Printing date 27.01.2015 Revision: 27.01.2015

(Contd. of page 4)

· Sensitisation: No sensitising effects known.

### SECTION 12: Ecological information

- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- $\cdot \textit{Additional ecological information:}$
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1950
	0.11-200
14.2 UN proper shipping name ADR	1950 AEROSOLS
IMDG	AEROSOLS
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1
IMDG, IATA	
Class	2.1
Label	2.1
14.4 Packing group	
ADR, IMDĞ, İATÂ	Void
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Gases.



Printing date 27.01.2015 Revision: 27.01.2015

(Contd. of page 5) · Danger code (Kemler): · EMS Number: F-D,S-U· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information:  $\cdot ADR$ 1L· Limited quantities (LQ) Code: E0 · Excepted quantities (EQ) Not permitted as Excepted Quantity · Transport category · Tunnel restriction code D· IMDG · Limited quantities (LQ) 1L· Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity UN1950, AEROSOLS, 2.1 · UN "Model Regulation":

### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H413 May cause long lasting harmful effects to aquatic life.

R12 Extremely flammable.

R53 May cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Gas 1: Flammable gases, Hazard Category 1

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas C: Gases under pressure: Compressed gas

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 4: Hazardous to the aquatic environment - Chronic Hazard, Category 4