

Printing date 06.04.2017 Revision: 06.04.2017 SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: Aerosol One 4 all diverse Farben · Article number (product ID.): REZ796 · 1.2 Relevant identified uses of the substance or mixture and uses advised against · Application of the substance / the mixture: painting · Uses advised against No further relevant information available. · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Peter Kwasny GmbH Heilbronner Str. 96 D-74831 Gundelsheim Tel.: 0049-(0)6269-95-20 E-mail: labor@kwasny.de · Further information obtainable from: Product safety department · 1.4 Emergency telephone number: Tel.:+49 6269 95 20 · national: National Poisons Information Service, Birmingham Tel.: 844 892 0111 · K-Nr. 0001 **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 GHS02 flame H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. Aerosol 1 GHS07 Eye Irrit. 2 H319 Causes serious eye irritation. Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. · Hazard pictograms GHS02 GHS07 · Signal word Danger · Hazard statements H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. H319 Causes serious eye irritation. H412 Harmful to aquatic life with long lasting effects. (Contd. on page 2)

- GB

Printing date 06.04.2017

Revision: 06.04.2017

Trade name: Aerosol One 4 all diverse Farben

	(Contd. of page 1)
• Precautionary s	statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P273	Avoid release to the environment.
<i>P305+P351+P</i> .	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Additional info	rmation:
Without adequa	te ventilation, explosive atmosphere/gas mix may be created.
EUH018 In use	may form flammable/explosive vapour-air mixture.
2.3 Other hazar	rds
Results of PBT	and vPvB assessment
PBT: Not appli	cable.

• **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

dimethyl ether	25-<50%
	10-<25%
🕐 Flam. Liq. 2, H225; 🕔 Eye Irrit. 2, H319	
2-butoxyethanol	1-<2.5%
Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	
trizinc bis(orthophosphate)	<1%
	 Flam. Gas 1, H220; Press. Gas C, H280 ethanol Flam. Liq. 2, H225; Eye Irrit. 2, H319 2-butoxyethanol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

 \cdot 4.1 Description of first aid measures

• After inhalation: Supply fresh air; consult doctor in case of complaints.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

GB

Printing date 06.04.2017

Revision: 06.04.2017

(Contd. of page 2)

Trade name: Aerosol One 4 all diverse Farben

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media -

· Suitable extinguishing agents: Cool container whit water

· For safety reasons unsuitable extinguishing agents: Water with full jet

- 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
 6.2 Methods and metarical for contribution and allowing straining and set of the second set of the se

- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace. Take note of emission threshold. Use only in well ventilated areas. Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Information about fire - and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
7.2 Conditions for safe storage, including any incompatibilities
Storage:
Requirements to be met by storerooms and receptacles: Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Protect from heat and direct sunlight.
- 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)

Printing date 06.04.2017

Revision: 06.04.2017

Trade name: Aerosol One 4 all diverse Farben

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

111-76-2 2-butoxyethanol

WEL Short-term value: 246 mg/m³, 50 ppm Long-term value: 123 mg/m³, 25 ppm Sk, BMGV

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BMGV 240 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: butoxyacetic acid

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Respiratory protection:

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply. **Protection of hands**:

• Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation


- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material
- Gloves must be changed after every contamination.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

 \cdot For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

butyl rubber, 0,7mm

· Eye protection:



(Contd. on page 5)

Printing date 06.04.2017

Revision: 06.04.2017

Trade name: Aerosol One 4 all diverse Farben

(Contd. of page 4)

9.1 Information on basic physical and ch	nemical properties
General Information	
Appearance: Form:	A
Form: Colour:	Aerosol According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Not applicable, as aerosol.
Flash point:	<0 °C
-	Without propellant gas.
Flammability (solid, gas):	Not applicable.
Ignition temperature:	235 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	3.0 Vol %
Upper:	18.6 Vol %
Vapour pressure at 20 °C:	3400 hPa
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	хт. • •тт 1• <i>0/</i> • 1, , •
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	52.1%
III and a man	With propellant gas. Content given by weight.
Water: VOC (EU)	2.4 % 52.04 %
Solids content:	43.5 %

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications. (Contd. on page 6)

- GB

Printing date 06.04.2017

Revision: 06.04.2017

(Contd. of page 5)

Trade name: Aerosol One 4 all diverse Farben

- · 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidising agents.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Possible in traces.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

7779-90-0 trizinc bis(orthophosphate)

Oral LD50 >5000 mg/kg (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation
- Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- $\cdot \textit{STOT-single exposure Based on available data, the classification criteria are not met.}$
- $\cdot \textbf{STOT-repeated exposure } Based on available data, the classification criteria are not met.$
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

7779-90-0 trizinc bis(orthophosphate)

LC50/96h 5100 µg/l (Oncorhynchus mykiss (Forelle))

- EC50 <1.7 mg/l (daphnia)
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Ikke relevant.
- 12.6 Other adverse effects No further relevant information available.

(Contd. on page 7)

Printing date 06.04.2017

Revision: 06.04.2017

Trade name: Aerosol One 4 all diverse Farben

(Contd. of page 6)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

15 01 10* packaging containing residues of or contaminated by hazardous substances

• Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	011750
ADR	1950 AEROSOLS
IMDG	AEROSOLS (trizinc bis(orthophosphate)), MARIN POLLUTANT
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1
IMDG	
Class	2.1
Label	2.1
IATA	
Class	2.1
Label	2.1
14.4 Packing group	
ADR, IMDG, IATA	Void not classified
14.5 Environmental hazards:	Product contains environmentally hazardous substances
	trizinc bis(orthophosphate)
Marine pollutant:	Symbol (fish and tree)

Printing date 06.04.2017

Revision: 06.04.2017

	(Cantil afree
	(Contd. of page
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	-
	not classified
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 litr
	Category A. For AEROSOLS with a capacity above 1 litr
	Category B. For WASTE AEROSOLS: Category C, Clea
	of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litr
	Segregation as for class 9. Stow "separated from" class
	except for division 1.4. For AEROSOLS with a capaci
	above 1 litre: Segregation as for the appropria
	subdivision of class 2. For WASTE AEROSOL. Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to A	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities $(\widetilde{E}Q)$	Code: E0
	Not permitted as Excepted Quantity
	I

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:

• Technical instructions (air):

Class	Share in %
Wasser	1-<2,5
NK	50-100

• Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 9)

GB

Printing date 06.04.2017

Revision: 06.04.2017

Trade name: Aerosol One 4 all diverse Farben

(Contd. of page 8)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
Department issuing SDS: Product safety department

· Contact: Hr. Hamberger · Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases - Category 1 Aerosol 1: Aerosols – Category 1 Press. Gas C: Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids - Category 2 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

 \cdot * Data compared to the previous version altered.