

Printing date 15.09.2017 Version number 52 Revision: 12.07.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name NEUKADUR MultiCast 1
- · Utilization of the substance of the formulation: Polyol for Polyurethanes
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

ALTROPOL KUNSTSTOFF GmbH

Rudolf-Diesel-Str 9 - 13 D-23617 Stockelsdorf Tel. +49 (0)451-49960-0 Fax. +49 (0)451-49960-20 e-mail: info@altropol.de

- · Further information obtainable from: environment protection department
- · 1.4 Emergency telephone number:

During normal opening times (7 am - 5 pm)

phone: +49 (0)451-49960-0

# SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard statements

H319 Causes serious eye irritation.

 $\cdot \textit{Precautionary statements}$ 

P280 Wear eye protection / face protection.P264 Wash thoroughly after handling.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

# SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 2)



Printing date 15.09.2017 Version number 52 Revision: 12.07.2017

### Trade name NEUKADUR MultiCast 1

David a service a service and service		(Contd. of page 1
· Dangerous components: CAS: 25214-63-5	Polyoxyalkylene Polyol	25 - 50%
Reg.nr.: 01-2119471485-32 01-2119471485-32	(1) Eye Irrit. 2, H319	
CAS: 25322-69-4	Polypropylenglykol	10 - 25%
CAS: 6846-50-0 Reg.nr.: 01-2119451093-47	1-Isopropyl-2,2-dimethyltrimethylendiisobutyrat Aquatic Chronic 3, H412	10-<25%
EC number: 918-167-1 Reg.nr.: 01-2119472146-39	Distillates (petroleum), hydrotreated light  Flam. Liq. 3, H226; Asp. Tox. 1, H304	5-<10%
	r the wording of the listed hazard phrases refer to section 16.	I

## SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Do not induce vomiting; call for medical help immediately.

*If swallowed, rinse mouth with water (only if the person is conscious).* 

A person vomiting while laying on their back should be turned onto their side.

Seek immediate medical advice.

- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- $\cdot$  5.2 Special hazards arising from the substance or mixture

*In case of fire, the following can be released:* 

Carbon monoxide (CO)

carbon dioxide

- · 5.3 Advice for firefighters
- · Protective equipment:

Wear fully protective suit.

Wear self-contained respiratory protective device.

· Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

## SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures
Particular danger of slipping on leaked/spilled product.

(Contd. on page 3)



Printing date 15.09.2017 Version number 52 Revision: 12.07.2017

### Trade name NEUKADUR MultiCast 1

(Contd. of page 2)

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

Ensure adequate ventilation

· 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Inform personnel of the affiliated with the product hazards and risks

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Open and handle receptacle with care.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Protect from heat.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage.
- · Requirements to be met by storerooms and receptacles:

Keep container tightly closed and dry and storage in a good ventilated room.

Storage temperature: 15 - 25 °C.

· Information about storage in one common storage facility:

Store away from reducing agents.

Do not store together with oxidising and acidic materials.

Store away from foodstuffs.

· Further information about storage conditions:

Protect from humidity and water.

Store in dry conditions.

 $Protect\ from\ frost.$ 

This product is hygroscopic.

- · Storage class: 10
- · 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

124-17-4 2-(2-butoxyethoxy)ethyl acetate

AGW (Germany) Long-term value: 67 mg/m³, 10 ppm

1.5(I);DFG, Y, 11

• Additional information: The lists valid during the making were used as basis.

(Contd. on page 4)



Printing date 15.09.2017 Version number 52 Revision: 12.07.2017

### Trade name NEUKADUR MultiCast 1

(Contd. of page 3)

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

- · Respiratory protection: Not necessary if room is well-ventilated.
- · Protection of hands:

Preventive skin protection (3-point program) required

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

# · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Suitable materials for protective gloves, EN 374-3:

*Polychloroprene - CR: thickness> = 0.5 mm, breakthrough time> = 480 min.* 

NBR - NBR: thickness> = 0,35 mm, Breakthrough time> = 480 min.

Butyl rubber - IIR: thickness> = 0.5 mm, breakthrough time> = 480 min.

Fluorine rubber - FKM: thickness> = 0.4 mm; breakthrough time> = 480 min.

Recommendation: Dispose of contaminated gloves ..

- · Eye protection: Goggles recommended during refilling
- · Body protection: Protective work clothing

# SECTION 9: Physical and chemical properties

· 9.	11	nf	ormai	ion	on	basi	ic pi	hysi	ical	and	C	hemi	ical	pro	pert	ies
------	----	----	-------	-----	----	------	-------	------	------	-----	---	------	------	-----	------	-----

· General Information

· Appearance:

Form: Fluid

Colour: According to product specification

· Odour: Characteristic · Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point:

Initial boiling point and boiling range: 175 °C

Flash point: > 100 °C
 Flammability (solid, gas): Not applicable.

· Ignition temperature: 210 °C

· Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

Undetermined.

· Explosion limits:

**Lower:** Not determined. Upper: Not determined.

(Contd. on page 5)



Printing date 15.09.2017 Version number 52 Revision: 12.07.2017

### Trade name NEUKADUR MultiCast 1

	(Conto	d. of page
· Vapour pressure:	Not determined.	
· Density at 20 °C:	0.95 g/cm³	
· Relative density	Not determined.	
· Vapour density	Not determined.	
Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Insoluble.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic at 20 °C:	85 mPas	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	13.7 %	
VOC (EC)	135.1 g/l	
· 9.2 Other information	No further relevant information available.	

# SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions

Reacts with reducing agents.

Reacts with oxidising agents.

Reacts with inorganic acid chlorides.

No dangerous reactions known.

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: Incompatible with oxidizing agents, acids
- · 10.6 Hazardous decomposition products:

Flammable gases/vapours

Carbon monoxide and carbon dioxide

# SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:				
25214-63	25214-63-5 Polyoxyalkylene Polyol				
Oral	LD50	>2000 mg/kg (Ratte)			
Dermal	LD50	>2000 mg/kg (Kaninchen)			
25322-69-	25322-69-4 Polypropylenglykol				
Oral	LD50	2000 mg/kg (Ratte)			
Dermal	LD50	10000 mg/kg (Kaninchen)			
Distillates	Distillates (petroleum), hydrotreated light				
Oral	LD50	>5000 mg/kg (Ratte)			
Dermal	LD50	>5000 mg/kg (Kaninchen)			
Inhalative	LC50/4 h	>4951 mg/l (Ratte)			

- · Primary irritant effect:
- · Skin corrosion/irritation slightly irritant (OECD method), labelling not required

(Contd. on page 6)



Printing date 15.09.2017 Version number 52 Revision: 12.07.2017

### Trade name NEUKADUR MultiCast 1

(Contd. of page 5)

· Serious eye damage/irritation

sligthly irritant, labelling not required (analogy conclusion)

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

### · 12.1 Toxicity

· 12.1 1 oxicity	· 12.1 Toxicuy				
· Aquatic toxi	· Aquatic toxicity:				
25214-63-5	25214-63-5 Polyoxyalkylene Polyol				
LC50 (96 h)	4500 mg/l (Leuciscus)				
EC50 (24h)	1400  mg/l  (B)				
EL50 (48h)	>100 mg/l (Daphnia Magna)				
EC10	EC10 800 mg/l (Pseudomonas putida) (DIN EN ISO 8192)				
25322-69-4	25322-69-4 Polypropylenglykol				
EC50 (48 h)	EC50 (48 h) >100 mg/l (Daphnia Magna)				

- · 12.2 Persistence and degradability No further relevant information available.
- · Other information: Elimination by adsorption onto activated sludge
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not empty into drains.

In an appropriate facility or burn in an approved landfill

Dispose. All applicable local and national or regional rules.

 ${\it Must not be disposed together with household garbage. Do not allow product to reach sewage system.}$ 

Must be specially treated adhering to official regulations.

### · European waste catalogue

20 01 27\* paint, inks, adhesives and resins containing hazardous substances

(Contd. on page 7)



Printing date 15.09.2017 Version number 52 Revision: 12.07.2017

Trade name NEUKADUR MultiCast 1

(Contd. of page 6)

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information				
· 14.1 UN-Number · ADR, ADN, IMDG, IATA	Void			
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void			
· 14.3 Transport hazard class(es)				
· ADR, ADN, IMDG, IATA · Class	Void			
· 14.4 Packing group · ADR, IMDG, IATA	Void			
· 14.5 Environmental hazards: · Marine pollutant:	No			
· 14.6 Special precautions for user	Not applicable.			
· 14.7 Transport in bulk according to Annex II of  Marpol and the IBC Code  Not applicable.				
· UN ''Model Regulation'':	Void			

# SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



- · Signal word Warning
- · Hazard statements

H319 Causes serious eye irritation.

· Precautionary statements

P280 Wear eye protection / face protection.P264 Wash thoroughly after handling.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	10 - 25

(Contd. on page 8)



Printing date 15.09.2017 Version number 52 Revision: 12.07.2017

### Trade name NEUKADUR MultiCast 1

(Contd. of page 7)

- · Waterhazard class: Water hazard class 1 (VwVwS 17.05.99): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

## · Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

· Department issuing SDS: environment protection department

#### · Contact:

Herr Karasmann Tel. +49 (0)451-49960-0 Herr Grützmacher Tel. +49 (0)2056-25863-6

### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity – Category 4

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

 $A quatic\ Chronic\ 3:\ Hazardous\ to\ the\ aquatic\ environment\ -\ long-term\ aquatic\ hazard\ -\ Category\ 3$ 

· \* Data compared to the previous version altered.

GB